

2/5/2013

Slimline Thermoplastic LED Exit Sign

Features

- Ultra-compact, low-profile design in neutral finish
- Energy-efficient LED technology
- EZ snap-out chevron directional indicators
- UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes

Electrical

- Dual 120V/277V voltage
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- LVD (low voltage disconnect) prevents battery from deep discharge
- Long-life, maintenance-free, rechargeable NiCd battery
- Internal solid-state transfer switch automatically connects the internal battery to LED Board for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

Electrical Information

Typical Performance	Red/Green	
	Input Voltage	120
Input Current (A)	0.9	0.9
Input Power (W)	0.8	0.8

Project:	
Catalog#:	
Approved by:	



Illumination

- Ultra-bright, energy efficient, long-lasting Red or Green LED.

Housing

- Injection-molded, engineering-grade, V-0 flame retardant, high-impact, thermoplastic in white or black finish
- Curved face, rounded corner design

Mounting

- Universal surface mount, wall or ceiling, with EZ-snap thermoplastic mounting canopy, which snaps into place making installation quick & easy.

Dimensions



ORDERING INFORMATION

Model Family #	Operation	Number of Faces	Letter Color	Housing Color	Options
HL0301	Blank - AC Only B - Battery Backup	2 - Double Face	R - Red G - Green	W - White B - Black	RC - Remote Capability

Example model# HL0301 B 2 R W

Specifications subject to change without notice.



Exit Sign