

3/21/2017

LIMITED QUANTITIES AVAILABLE

High Bay Acrylic 22"

(Open Bottom Reflector)

HPS / 400 watts | PS / 320 - 400 watts | MH / 400 watts

Applications

Ideal for lighting warehouses, industrial, and retail facilities

Features

- Die-cast housing with electrical box (lamp included)
- Adjustable accessory bracket

Project:	
Catalog#:	
Approved by:	



HID/CFL Fixtures

ORDERING INFORMATION

Catalog #	Watts	Volts †	Ballast	ANSI	Lamp Part #
HAC220-400-HPS-4T	400 HPS	4T	CWA	S51	LU400
HAC220-320-PS-4T	320 PSMH	4T	PS-CWA	M154/O	MP320/BU/PS
HAC220-400-PS-4T	400 PSMH	4T	PS-CWA	M155/O	MP400/BU/PS
HAC220-400-MH-4T	400 MH	4T	CWA	M59/O	MP400/BU
HAC220-350-PS-4T	350PSMH	4T	PS-CWA	M131/O	MP350/BU/PS

ACCESSORIES (sold separately)

Catalog #	Description
22WG	Wire guard with stainless steel construction
22FA	22" flat acrylic
22CB	22" clamp band
QR	120v quartz restrrike with socket, bracket, and dual contact bayonet (250 watt halogen lamp included)
HL	250 watt halogen lamp (fits 120v restrrike socket and bracket)
SC	Insulated 3' steel safety cable with clear vinyl coating (includes a steel eye on one end and a loop on the opposite end)
SSH2	Malleable screw-shut hook
SPMRP	Swivel pendent mount round plate with a ball that allows the fixture to hang straight (mount to standard electrical box; fits 3/4" conduit)
22CLR	Collar for 22" acrylic refractor

FACTORY INSTALLED OPTIONS

Catalog #	Description	Accessory Code *
CS120	120v cordset with NEMA L5-15 twist lock plug (custom lengths available)	B



* When ordering, include the Accessory Code with the catalog number
 ONLY available with models: (HAC220-320-PS-4T-B & HAC220-400-PS-4T-B)

† 4T = 120, 208, 240, 277 volts (pre-wired to 277)

Specifications subject to change without notice.



DIMENSIONS



PHOTOMETRICS

