

Medium-Base LED Replacement Lamp
3000K, 4000K / 15W, 19W, 24W / 130 Lm/W

Project:	
Catalog#:	
Approved by:	



No Ballast needed (UL Type B)
Internal driver/line voltage lamp
Remove ballast from fixture

Features

- 130 Lm/W
- 360° Beam Angle (Omni Directional)
- Power Factor: >0.9
- CCT: 3000K or 4000K; CRI: >80
- Long Life: 10 years
- Operating temperature range: -40 to +60°C
- IP64 Design - Driver is fully potted with silicone.
- Waterproof, dust proof, and bug proof
- Flame retardant material
- UL/cUL Listed, UL Classified
- 120-277 VAC, 50/60Hz
- Built-in 4kV surge protection
- Non-dimming
- Warranty: 5 Years



Includes Mogul Base to Medium Base Socket Reducer
(E39 - E26)

Applications



Wallpack



Acorn



Pendant



Posttop



Ball



Floodlight



Posttop



Garage Light



Ordering Information

Catalog #	Lumens	CCT	Watts	Lm/W	Cover	Base	Replacement
LEDMEDR-3015-MV	1950	3000	15	130	Clear	E26 MED	50W HPS or MH
LEDMEDR-4015-MV	1950	4000	15	130	Clear	E26 MED	50W HPS or MH
LEDMEDR-3019-MV	2470	3000	19	130	Clear	E26 MED	70W HPS or MH
LEDMEDR-4019-MV	2470	4000	19	130	Clear	E26 MED	70W HPS or MH
LEDMEDR-3024-MV	3120	3000	24	130	Clear	E26 MED	100W HPS or MH
LEDMEDR-4024-MV	3120	4000	24	130	Clear	E26 MED	100W HPS or MH

Medium-Base LED Replacement Lamp
3000K, 4000K / 15W, 19W, 24W / 130 Lm/W

Project:	
Catalog#:	
Approved by:	

Dimensions (in)



LEDMEDR vs. Common Lamp Sizes

Lamp	Base	L (in.)	D (in.)
LEDMEDR-XX15-MV	E26 (default)	5.67	2.52
LEDMEDR-XX19-MV		6.1	
LEDMEDR-XX24-MV		6.65	
LEDMEDR-XX15-MV	w/ adapter (Adds 0.9 inch)	6.57	2.52
LEDMEDR-XX19-MV		7.0	
LEDMEDR-XX24-MV		7.55	
LU100	E39	7.75	2.94
LU150/55		3.5	8.31
MH150/U			
MH175/U			
H39KB-175			
H37KC-175/DX		8.25	

